

HARDWOOD WORK SURFACES

PRODUCT DEFINITION

Ideal for electrical, industrial, or dye work, hardwood tops offer a rugged, yet yielding surface for precision tools. Crafted using face-glued strips, then sanded to a smooth finish, the hardwood top offers a strong countertop with a quality appearance.

Tops are coated with catalyzed clear lacquer, 5 top coats and 2 bottom coats.



Hardwood Work Surfaces are 1 3/4" thick.

Hardwood Shelves and Back Guards are 1 1/4" thick.

Work surfaces and shelves are available in sizes up to 36" x 96".
Tops with field joints are available up to 60" x 96".

Edge is 1/8" eased edge.

CATALYZED LACQUER TEST RESULTS

CHEMICAL	RATING
SULFURIC ACID 25%	5
SULFURIC ACID 50%	5
ACETIC ACID 50%	4
ACETIC ACID 75%	4
PHOSPHORIC ACID 50%	5
PHOSPHORIC ACID 75%	5
HYDROCHLORIC ACID 20%	5
HYDROCHLORIC ACID 37%	4
BUTYL ALCOHOL	5
ETHYL ALCOHOL	5
METHYL ALCOHOL	5
ETHYL ACETATE	2
METHYL ETHYL KETONE	1
TOLUENE	5
ACETONE	1
NAPHTHA	5
XYLENE	5
SODIUM HYPOCHLORITE 5.25%	5
SODIUM HYDROXIDE 25%	5
SODIUM HYDROXIDE 35%	5
SODIUM HYDROXIDE 40%	5
SODIUM HYDROXIDE 50%	5
POTASSIUM HYDROXIDE 40%	5
POTASSIUM HYDROXIDE 45%	5
HYDROGEN PEROXIDE 30%	5
NITRIC ACID 25%	5

Test prepared by Sheboygan Paint Co 1/2009

5 = No Effect
 4 = Slight Stain
 3 = Modest Stain
 2 = Modest Stain, Film Blistered
 1 = Film Damage